

ASTON MARTIN RAPIDE RAPIDE S (2013-2014)

**ENGINE**

Capacity: 11 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Helar 0W-40***Change every 16000 km/ 12 months***DIFFERENTIAL REAR LIMITED SLIP**

Capacity: 1,6 liter, Capacity: 118 CM3 (LS-additive)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear LS 1015***Change every 64000 km/ 48 months***TRANSMISSION AUTOMATIC ZF 6HP26 6/1**

Capacity: 9,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Matic 4026***Check every 16000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-S DOT 4***Change every 16000 km/ 12 months***POWER STEERING**

Capacity: 1,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Fluid 3013***Check every 16000 km/ 12 months*

ASTON MARTIN RAPIDE RAPIDE S (2013-2014)



COOLING SYSTEM

Capacity: 15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 16000 km/ 12 months, change every 160000 km/ 60 months

AIRCONDITIONING

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.