

AUDI (EU) 100, S4 100 2.4 D (1992-1994)



MOTOR AAS
Kapacitet: 5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Specialsynth MSP 5W-40

PRODUKTANBEFALING 2
Emperol 5W-40

PRODUKTANBEFALING 3
Emperol 10W-40

Skift alle 7500 km/ 12 måneder

TRANSAKSEL MANUEL 012 / 01W / 0A9 5/1
Kapacitet: 2,25 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Gear 1011

PRODUKTANBEFALING 2
Syngear TDL 75W-90

Kontroller alle 15000 km/ 12 måneder

HYDRAULISK SYSTEM SERVOSTYRING/NIVELLERING
Kapacitet: 2,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Fluid 3013

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2
Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING
Kapacitet: 1,1 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1
SP Fluid 3013

AUDI (EU) 100, S4 100 2.4 D (1992-1994)



KØLESYSTEM

Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant -38 Organic NF

Skift alle 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.