PRODUCT RECOMMENDATION

# AUDI (EU) 100, S4 100 2.8E (1992-1994)

## ENGINE AAH
Capacity: 5 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | **PRODUCT RECOMMENDATION 3** |
| **Helar SP LL-03 0W-30** | **Helar SP LL-03 5W-30** | **Helar 0W-40** |
| *Change every 15000 km/ 12 months* | | |

| USE | | CLIMATE |
|---|---|---|
| Normal | | Cold |
| **PRODUCT RECOMMENDATION 1** | | |
| **Presteza MSP 5W-30** | | |
| *Change every 15000 km/ 12 months* | | |

## DIFFERENTIAL FROM AUTOMATIC
Capacity: 1 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **SP Gear 1011** | **Syngear TDL 75W-90** | |
| *Check every 15000 km/ 12 months* | | |

## TRANSAXLE MANUAL 5/1
Capacity: 2,35 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | **PRODUCT RECOMMENDATION 2** | |
| **SP Gear 1011** | **Syngear TDL 75W-90** | |
| *Check every 15000 km/ 12 months* | | |

## TRANSMISSION AUTOMATIC 4/1
Capacity: 2,7 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| **PRODUCT RECOMMENDATION 1** | | |
| **ATF Dexron II-D** | | |
| *Check every 30000 km/ 12 months, change every 60000 km/ 48 months* | | |

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# AUDI (EU) 100, S4 100 2.8E (1992-1994)

## HYDRAULIC SYSTEM POWER STEERING/LEVELLING
Capacity: 2,5 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **SP Fluid 3013** | | |

## HYDRAULIC BRAKE/CLUTCH SYSTEM

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
|---|---|---|
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Change every 24 months*

## POWER STEERING
Capacity: 1,1 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **SP Fluid 3013** | | |

## COOLING SYSTEM
Capacity: 11 liter

| USE | CLIMATE |
|---|---|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | | |
|---|---|---|
| **Coolant -38 Organic NF** | | |

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367