

# AUDI (EU) A4 ALLROAD 8WH A4 ALLROAD 2.0 TDI QUATTRO (140 KW) (2016-2019)



**ENGINE** DESA, DETA  
Capacity: 4,7 liter

| USE                  | CLIMATE  |
|----------------------|----------|
| Extended drain (max) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |
|-----------------------------|-----------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |

*Change every 30000 km/ 24 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |
|-----------------------------|-----------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |

*Change every 15000 km/ 12 months*

**DIFFERENTIAL REAR**  
Capacity: 0,67 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**TRANSAXLE SEMI-AUTOMATIC S TRONIC CLUTCH PART** 0CL  
Capacity: 4,35 liter (Dry fill), Capacity: 3,5 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>SP Matic 2072</b>     |  |

**TRANSAXLE SEMI-AUTOMATIC S TRONIC TRANSMISSION** 0CL 7/1  
Capacity: 3,8 liter (Dry fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>SP Matic 2072</b>     |  |

## HYDRAULIC BRAKE SYSTEM

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         |  |
|----------------------------------|--|
| <b>Drauliquid-LV Super DOT 4</b> |  |

*Change every 24 months*

**AUDI (EU) A4 ALLROAD 8WH A4 ALLROAD  
2.0 TDI QUATTRO (140 KW) (2016-2019)****COOLING SYSTEM**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| Coolant SP 12 EVO        |  |          |

*Check every 24 months/ 30000 km*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*