

AUDI (EU) A4, S4, RS 4 8E A4 2.8 VR6 (128 KW) (2003-2005)



MOTOR BCZ
Kapacitet: 5,5 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Helar 0W-40

PRODUKTANBEFALING 2

Emperol 5W-40

PRODUKTANBEFALING 3

Asyntho 5W-30

Skift alle 30000 km/ 24 måneder

DIFFERENTIAL CVT
Kapacitet: 1,3 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1071

Kontroller alle 24 måneder/ 30000 km

TRANSAKSEL CVT 01J 1/1
Kapacitet: 7,7 liter

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Matic 4016

Skift alle 60000 km

TRANSAKSEL MANUEL 0A2 6/1

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Kontroller alle 30000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND
Normal

KLIMA
Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

AUDI (EU) A4, S4, RS 4 8E A4 2.8 VR6 (128 KW) (2003-2005)



SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 24 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 12 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 12 EVO

Kontroller alle 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.