

AUDI (EU) A5, S5, RS 5 8T A5 2.0 TDI QUATTRO (125 KW) (2008-2011)



ENGINE CAHA
Capacity: 5 liter

USE

Extended drain (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30*Change every 30000 km/ 24 months*

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 0W-30

PRODUCT RECOMMENDATION 2

Helar SP LL-03 5W-30*Change every 15000 km/ 12 months*

DIFFERENTIAL REAR 0BC
Capacity: 0,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

TRANSAXLE MANUAL/TRANSFERBOX 0B2 6/1
Capacity: 4,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

AUDI (EU) A5, S5, RS 5 8T A5 2.0 TDI QUATTRO (125 KW) (2008-2011)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

Check every 24 months/ 30000 km

COOLING SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 12 EVO		

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.