AUDI (EU) A5, S5, RS 5 CABRIOLET 8F7 A5 CABRIOLET 2.0 TDI (125 KW) (2009-2011)



ENGINE CAHA Capacity: 5 liter		
USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 30000 km/ 24 months		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	
Change every 15000 km/ 12 months		

TRANSAXLE MANUAL 0B1 6/1 Capacity: 4 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear 5015	

Check every 24 months/ 30000 km

HYDRAULIC ACTUATION CONVERTIBLE ROOF		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

HYDRAULIC BRAKE/CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	

AUDI (EU) A5, S5, RS 5 CABRIOLET 8F7 A5 CABRIOLET 2.0 TDI (125 KW) (2009-2011)



POWER STEERING		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		
Check every 24 months/ 30000 km	·	

COOLING SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 12 EVO	
Check every 24 months/ 30000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.