

AUDI (EU) A5, S5, RS 5 CABRIOLET 8F7 A5 CABRIOLET 2.0 TDI QUATTRO (140 KW) (2014-2017)



ENGINE CDDA, CNHA
Capacity: 4,7 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30

Change every 15000 km/ 12 months

DIFFERENTIAL REAR 0BC
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Gear 1011	Syngear TDL 75W-90

Change every 30000 km/ 24 months

TRANSAXLE MANUAL/TRANSFERBOX 0B2 6/1
Capacity: 4,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 2072	

Check every 24 months/ 30000 km

HYDRAULIC ACTUATION CONVERTIBLE ROOF

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

AUDI (EU) A5, S5, RS 5 CABRIOLET 8F7 A5 CABRIOLET 2.0 TDI QUATTRO (140 KW) (2014-2017)



HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4*Change every 24 months*

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO*Check every 24 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.