

AUDI (EU) A6 ALLROAD 4G A6 ALLROAD 3.0 TFSI QUATTRO (245 KW) (2014-2018)



ENGINE CREC, CTDA
Capacity: 6,8 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1

Helar SP LL-03 5W-30

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Helar 0W-40

PRODUCT RECOMMENDATION 2

Emperol 5W-40

PRODUCT RECOMMENDATION 3

Asyntho 5W-30

Change every 15000 km/ 12 months

DIFFERENTIAL REAR
Capacity: 0,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

Check every 24 months/ 30000 km

DIFFERENTIAL REAR ACTUATION
Capacity: 0,85 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

Check every 24 months/ 30000 km

TRANSMISSION S TRONIC CLUTCH PART 0B5 (DL501)

Capacity: 7,5 liter (Dry fill, with oil cooler), Capacity: 7 liter (Dry fill, without oil cooler), Capacity: 5,5-6 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072

Check every 24 months/ 30000 km

AUDI (EU) A6 ALLROAD 4G A6 ALLROAD 3.0 TFSI QUATTRO (245 KW) (2014-2018)



TRANSMISSION S TRONIC TRANSMISSION PART 0B5 (DL501) 7/1

Capacity: 4,35 liter (Dry fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2072

Check every 24 months/ 30000 km

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Check every 30000 km/ 12 months, change every 24 months

COOLING SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12 EVO

Check every 24 months/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.