

AUDI (EU) A6, S6, RS 6 4B A6 2.5 TDI V6 (110 KW) (2000-2005)



MOTOR AFB
Kapacitet: 5,5 liter

ANVEND

Forlænget interval (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Skift alle 35000 km/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 5W-30

PRODUKTANBEFALING 2

Presteza MSP 5W-30

PRODUKTANBEFALING 3

Specialsynth MSP 5W-40

Skift alle 15000 km/ 12 måneder

ANVEND

Normal

KLIMA

Koldt

PRODUKTANBEFALING 1

Emperol 5W-40

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE FRA EN AUTOMATISK

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Kontroller alle 70000 km

GEAR AUTOMATISK 01V 5/1

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

PRODUKTANBEFALING 2

SP Matic 2032

Kontroller alle 35000 km

AUDI (EU) A6, S6, RS 6 4B A6 2.5 TDI V6 (110 KW) (2000-2005)



TRANSAXSEL MANUEL 6/1

Kapacitet: 2,4 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Kontroller alle 35000 km

HYDRAULISK BREMSESYSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 24 måneder

SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KØLESYSTEM

Kapacitet: 6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12

PRODUKTANBEFALING 2

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.