

AUDI (EU) A6, S6, RS 6 4F A6 2.8 FSI QUATTRO (162 KW) (2008-2011)



MOTOR CCEA

Kapacitet: 6,2 liter (Servicepåfyldning)

ANVEND	KLIMA
Forlænget interval (max)	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Skift alle 30000 km/ 24 måneder

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Helar 0W-40	Emperol 5W-40	Asyntho 5W-30

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE FRA EN AUTOMATISK

Kapacitet: 1,1 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 60000 km/ 24 måneder

GEAR AUTOMATISK 09L 6/1

Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2034		

Kontroller alle 24 måneder/ 30000 km

TRANSAKSEL MANUEL/REDUKTIONSGEARKASSE 02X 6/1

Kapacitet: 3,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Matic 2072		

Kontroller alle 24 måneder/ 30000 km

AUDI (EU) A6, S6, RS 6 4F A6 2.8 FSI QUATTRO (162 KW) (2008-2011)



TRANSFERGEARKASSE FRA AUTOMATISK

Kapacitet: 0,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear LS 1015

Kontroller alle 24 måneder/ 30000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 24 måneder

SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.