

AUDI (EU) A6, S6, RS 6 4F A6 3.0 QUATTRO (2005-2006)



ENGINE BBJ
Capacity: 6,3 liter

USE		CLIMATE
Extended drain (max)		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Change every 30000 km/ 24 months

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40

Change every 15000 km/ 12 months

USE		CLIMATE
Normal		Cold
PRODUCT RECOMMENDATION 1		
Presteza MSP 5W-30		

Change every 15000 km/ 12 months

DIFFERENTIAL FROM AUTOMATIC
Capacity: 1,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 24 months/ 30000 km

DIFFERENTIAL REAR

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 24 months/ 30000 km

AUDI (EU) A6, S6, RS 6 4F A6 3.0 QUATTRO (2005-2006)

**TRANSAXLE AUTOMATIC 09L 6/1**

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034

Check every 24 months/ 30000 km

TRANSFERBOX FROM AUTOMATIC

Capacity: 0,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

Check every 24 months/ 30000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

Change every 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013**COOLING SYSTEM**

Capacity: 12 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.