

AUDI (EU) A7, S7, RS 7 4G A7 3.0 TDI QUATTRO (235 KW) (2014-2018)



MOTOR CVUA
Kapacitet: 6,4 liter

ANVEND

Forlænget interval (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Skift alle 30000 km/ 24 måneder

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

Skift alle 15000 km/ 12 måneder

DIFFERENTIALE BAG

Kapacitet: 0,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Kontroller alle 24 måneder/ 30000 km

DIFFERENTIALE BAG AKTIVERING

Kapacitet: 0,85 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1081

Kontroller alle 24 måneder/ 30000 km

DIFFERENTIALE FRA EN AUTOMATISK

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

AUDI (EU) A7, S7, RS 7 4G A7 3.0 TDI QUATTRO (235 KW) (2014-2018)



GEAR AUTOMATISK 0BK 8/1

Kapacitet: 3,6-4 liter (Servicepåfyldning), Kapacitet: 8,6-9 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 2034

TRANSFERGEARKASSE FRA AUTOMATISK

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear LS 1015

HYDRAULISK BREMSESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Kontroller alle 30000 km/ 12 måneder, skift alle 24 måneder

KØLESYSTEM

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 12 EVO

Kontroller alle 24 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.