

AUDI (EU) A8, S8 4D A8 2.5 V6 TDI QUATTRO (132 KW) (1999-2003)



MOTOR AKE, BAU, BDH
Kapacitet: 5,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Skift alle 35000 km/ 24 måneder

DIFFERENTIALE BAG
Kapacitet: 1,5 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Gearlube GL-5 80W-90		

Kontroller alle 35000 km

DIFFERENTIALE FRA EN AUTOMATISK
Kapacitet: 0,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 70000 km

GEAR AUTOMATISK 01V 5/1
Kapacitet: 9 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Matic 4026	SP Matic 2032	

Kontroller alle 35000 km

TRANSKSEL MANUEL 6/1
Kapacitet: 2,4 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 35000 km

AUDI (EU) A8, S8 4D A8 2.5 V6 TDI QUATTRO (132 KW) (1999-2003)



TRANSFERGEARKASSE FRA AUTOMATISK

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
SP Gear 1011	Syngear TDL 75W-90	

Kontroller alle 35000 km

HYDRAULISK SYSTEM SERVOSTYRING/SERVOBREMSE/NIVELLERING

Kapacitet: 2,7 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 70000 km

HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 24 måneder

KØLESYSTEM

Kapacitet: 10 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Coolant SP 12	Coolant SP 12 EVO	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.