

# AUDI (EU) Q5, SQ5 8R Q5 2.0 TDI QUATTRO (125 KW) (2010-2012)

**MOTOR** CGLB, CMGA

Kapacitet: 5 liter (Servicepåfyldning)

| ANVEND                   | KLIMA   |
|--------------------------|---------|
| Forlænget interval (max) | Moderat |

## PRODUKTANBEFALING 1

**Helar SP LL-03 0W-30**

## PRODUKTANBEFALING 2

**Helar SP LL-03 5W-30***Skift alle 30000 km/ 24 måneder*

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

## PRODUKTANBEFALING 1

**Helar SP LL-03 0W-30**

## PRODUKTANBEFALING 2

**Helar SP LL-03 5W-30***Skift alle 15000 km/ 12 måneder***DIFFERENTIALE BAG** 0BC

Kapacitet: 0,9 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

## PRODUKTANBEFALING 1

**SP Gear 1011**

## PRODUKTANBEFALING 2

**Syngear TDL 75W-90****GEAR S-TRONIC GEARKASSEDEL** 0B5 (DL501) 7/1

Kapacitet: 4,35 liter (Tør efterfyld)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

## PRODUKTANBEFALING 1

**SP Matic 2072****GEAR S-TRONIC KOBLINGSDEL** 0B5 (DL501)

Kapacitet: 6,7 liter (Servicepåfyldning), Kapacitet: 7 liter (Tørfyldning, uden oliekløler), Kapacitet: 7,5 liter (Tøropfyldning, med oliekløler)

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

## PRODUKTANBEFALING 1

**SP Matic 2072**

# AUDI (EU) Q5, SQ5 8R Q5 2.0 TDI QUATTRO (125 KW) (2010-2012)



## TRANSAXSEL MANUEL/REDUKTIONSGEARKASSE 0B2 6/1

Kapacitet: 4,8 liter

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>SP Matic 2072</b> |  |         |

## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

| ANVEND                           |  | KLIMA   |
|----------------------------------|--|---------|
| Normal                           |  | Moderat |
| PRODUKTANBEFALING 1              |  |         |
| <b>Drauliquid-LV Super DOT 4</b> |  |         |

## SERVOSTYRING

| ANVEND               |  | KLIMA   |
|----------------------|--|---------|
| Normal               |  | Moderat |
| PRODUKTANBEFALING 1  |  |         |
| <b>SP Fluid 3013</b> |  |         |

Kontroller alle 60000 km/ 36 måneder

## KØLESYSTEM

Kapacitet: 9-10 liter

| ANVEND                   |  | KLIMA   |
|--------------------------|--|---------|
| Normal                   |  | Moderat |
| PRODUKTANBEFALING 1      |  |         |
| <b>Coolant SP 12 EVO</b> |  |         |

Kontroller alle 48 måneder/ 60000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.