

AUDI (EU) 80, RS 2 80 QUATTRO 1.8S (1987-1989)



ENGINE

Capacity: 3,5 liter, Filter capacity: 0,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30	Specialsynth MSP 5W-40	Emperol 5W-40

Change every 15000 km/ 12 months

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Presteza MSP 5W-30		

Change every 15000 km/ 12 months

DIFFERENTIAL REAR

Capacity: 2,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Gearlube GL-5 80W-90		

Check every 15000 km/ 12 months

TRANSAXLE MANUAL/TRANSFERBOX 4/1

Capacity: 2,85 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

Check every 1500 km/ 12 months

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

AUDI (EU) 80, RS 2 80 QUATTRO 1.8S (1987-1989)**POWER STEERING**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

COOLING SYSTEM

Capacity: 6,5 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.