

# AUDI (EU) A5, S5, RS 5 CABRIOLET 8F7 A5 CABRIOLET 3.0 TDI QUATTRO (176 KW) (2009-2012)



**ENGINE** CCWA, CCLA  
Capacity: 6,9 liter

| USE                  | CLIMATE  |
|----------------------|----------|
| Extended drain (max) | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |
|-----------------------------|-----------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |

*Change every 30000 km/ 24 months*

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1    | PRODUCT RECOMMENDATION 2    |
|-----------------------------|-----------------------------|
| <b>Helar SP LL-03 0W-30</b> | <b>Helar SP LL-03 5W-30</b> |

*Change every 15000 km/ 12 months*

**DIFFERENTIAL REAR** 0BC  
Capacity: 0,9 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2  |
|--------------------------|---------------------------|
| <b>SP Gear 1011</b>      | <b>Syngear TDL 75W-90</b> |

*Check every 24 months/ 30000 km*

## DIFFERENTIAL REAR ACTUATION

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>SP Gear 1081</b>      |  |

## TRANSMISSION S TRONIC CLUTCH PART 0B5 (DL501)

Capacity: 7,5 liter (Dry fill, with oil cooler), Capacity: 7 liter (Dry fill, without oil cooler), Capacity: 6,7 liter (Service fill)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 |  |
|--------------------------|--|
| <b>SP Matic 2072</b>     |  |

# AUDI (EU) A5, S5, RS 5 CABRIOLET 8F7 A5 CABRIOLET 3.0 TDI QUATTRO (176 KW) (2009-2012)


**TRANSMISSION S TRONIC TRANSMISSION PART 0B5 (DL501) 7/1**

Capacity: 4,35 liter (Dry fill)

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Matic 2072</b>     |  |          |

**HYDRAULIC ACTUATION CONVERTIBLE ROOF**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

**HYDRAULIC BRAKE SYSTEM**

| USE                              |  | CLIMATE  |
|----------------------------------|--|----------|
| Normal                           |  | Moderate |
| PRODUCT RECOMMENDATION 1         |  |          |
| <b>Drauliquid-LV Super DOT 4</b> |  |          |

*Change every 24 months*
**POWER STEERING**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>SP Fluid 3013</b>     |  |          |

*Check every 24 months/ 30000 km*
**COOLING SYSTEM**

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Coolant SP 12 EVO</b> |  |          |

*Check every 24 months/ 30000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.