

PRODUCT RECOMMENDATION

AUDI (EU) A8, S8 4D A8 4.2 V8 32V QUATTRO (210 KW) (1995-1999)

**ENGINE AGH**

Capacity: 7,5 liter, Filter capacity: 0,5 liter

USE	CLIMATE
Extended drain (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	

Change every 30000 km/ 24 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 0W-30	Helar SP LL-03 5W-30	Helar 0W-40

Change every 15000 km/ 12 months

USE	CLIMATE
Normal	Cold

PRODUCT RECOMMENDATION 1		
Presteza MSP 5W-30		

*Change every 15000 km/ 12 months***DIFFERENTIAL FROM AUTOMATIC**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

*Check every 60000 km***DIFFERENTIAL REAR**

Capacity: 1,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

*Check every 30000 km***TRANSFERBOX FROM AUTOMATIC**

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

PRODUCT RECOMMENDATION

AUDI (EU) A8, S8 4D A8 4.2 V8 32V QUATTRO (210 KW) (1995-1999)



TRANSMISSION AUTOMATIC 018 4/1

Capacity: 9,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032

Check every 30000 km

TRANSMISSION AUTOMATIC 01L 5/1

Capacity: 9,8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

PRODUCT RECOMMENDATION 2

SP Matic 2032

Check every 30000 km

HYDRAULIC SYSTEM POWER STEERING/BRAKE BOOSTER/LEVELLING

Capacity: 2,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 60000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 24 months

COOLING SYSTEM

Capacity: 9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 12

PRODUCT RECOMMENDATION 2

Coolant SP 12 EVO

PRODUCT RECOMMENDATION

**AUDI (EU) A8, S8 4D A8 4.2 V8 32V
QUATTRO (210 KW) (1995-1999)**



The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.