## **AUDI (EU) COUPÉ, S2 COUPÉ GT 2.2** (1986-1988)



ENGINE KU Capacity: 3 liter, Filter capacity: 0,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Helar SP LL-03 5W-30 Specialsynth MSP 5W-40		Emperol 5W-40
Change every 15000 km/ 12 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Presteza MSP 5W-30		
Change every 15000 km/ 12 months		

DIFFERENTIAL FROM AUTOMAT Capacity: 0,75 liter	IC	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Check every 15000 km/ 12 months	•	

TRANSAXLE MANUAL 5/1 Capacity: 2,35 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
Check every 15000 km/ 12 months			

TRANSMISSION AUTOMATIC 3/1 Capacity: 3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		
Check every 15000 km/ 12 months, change every 30000 km/ 24 months		

PRODUCT RECOMMENDATION

## **AUDI (EU) COUPÉ, S2 COUPÉ GT 2.2** (1986-1988)



HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change of any 24 months			

Change every 24 months

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.