

BENTLEY BROOKLANDS BROOKLANDS/R

(1992-1999)

**ENGINE**

Capacity: 9,4 liter, Filter capacity: 1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Emperol 10W-40****PRODUCT RECOMMENDATION 2****Bi-Turbo 15W-40****PRODUCT RECOMMENDATION 3****Bi-Turbo 20W-50***Change every 12500 km/ 6 months***DIFFERENTIAL REAR**

Capacity: 2,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Gearlube GL-5 80W-90***Change every 50000 km/ 36 months***TRANSMISSION AUTOMATIC**

Capacity: 4,25 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D***Change every 25000 km/ 12 months***HYDRAULIC SYSTEM BRAKES/LEVELLING**

Capacity: 5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**LHM +***Change every 100000 km/ 72 months***POWER STEERING**

Capacity: 0,75 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**ATF Dexron II-D***Check every 12500 km*

BENTLEY BROOKLANDS BROOKLANDS/R

(1992-1999)

**COOLING SYSTEM**

Capacity: 18 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF***Change every 50000 km/ 36 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.