## **BENTLEY CONTINENTAL, AZURE AZURE**

(1994-2003)



<b>ENGINE</b> Capacity: 9,4 liter, Filter capacity: 1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Emperol 10W-40	Bi-Turbo 15W-40	Bi-Turbo 20W-50
Emperol 10W-40	BI-Turbo 15W-40	BI-1 urbo 20W-50

Change every 12500 km/6 months

DIFFERENTIAL REAR Capacity: 2,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube GL-5 80W-90	
Change every 50000 km/ 36 months	<u> </u>

TRANSMISSION AUTOMATIC Capacity: 4,25 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Change every 25000 km/ 12 months	

HYDRAULIC SYSTEM BRAKES/LEVELLING Capacity: 5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
LHM +			
Change every 100000 km/ 72 months			

POWER STEERING Capacity: 0,75 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 12500 km	

## **BENTLEY CONTINENTAL, AZURE AZURE**

(1994-2003)



COOLING SYSTEM Capacity: 18 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change avery 50000 km/ 26 months	

Change every 50000 km/36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.