

BMW (EU) SERIE 3 E90 / E91 / E92 320i (125 KW) (2007-2013)



MOTOR N43

Kapacitet: 4,25 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Helar SP LL-03 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 5W-30

PRODUKTANBEFALING 3

Presteza MSP 5W-30

Skift alle 25000 km/ 24 måneder

DIFFERENTIALE BAG FRA OG MED 07/2011

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

DIFFERENTIALE BAG OP TIL 07/2011

Kapacitet: 0,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

GEAR AUTOMATISK ZF 6HP19 6/1

Kapacitet: 9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

GEAR MANUEL Getrag GS6-17BG/DG 6/1

Kapacitet: 1,4 liter (Førstegangsopfyldning), Kapacitet: 1,3 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

BMW (EU) SERIE 3 E90 / E91 / E92 320i (125 KW) (2007-2013)



HYDRAULISK BREMSE/KOBLINGSSYSTEM DSC

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Skift alle 24 måneder

ANVEND	KLIMA
Krævende	Moderat

PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Skift alle 12 måneder

SERVOSTYRING MED AFS/ARS (CHF-DÆKSEL)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
SP Fluid 3013		

SERVOSTYRING SEPARAT SYSTEM

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
ATF Dexron II-D		

KØLESYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1		
Coolant SP 11		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.