

BMW (EU) 4 SERIES F32 / F82 428I XDRIVE (2013-2016)



ENGINE N20B20
Capacity: 4,8-5 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 0W-20

PRODUCT RECOMMENDATION 2

Presteza MSP 0W-30

PRODUCT RECOMMENDATION 3

Helar SP LL-03 0W-30

Change every 30000 km/ 24 months

DIFFERENTIAL FRONT

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071**DIFFERENTIAL REAR**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90**TRANSFERBOX ATC 35L**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081**TRANSMISSION AUTOMATIC ZF GA8HP 8/1**

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 2034

BMW (EU) 4 SERIES F32 / F82 428I XDRIVE (2013-2016)


TRANSMISSION MANUAL ZF GS6X45BZ/DZ 6/1

Capacity: 1,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2072		

HYDRAULIC BRAKE/CLUTCH SYSTEM DSC

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid-LV Super DOT 4		

Change every 24 months

COOLING SYSTEM

Capacity: 9,1 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 11		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.