

BMW (EU) X5 F15 / F85 X5 XDRIVE35I (225 KW) (2013-2018)



MOTOR N55B30
Kapacitet: 6,5 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 0W-30

PRODUKTANBEFALING 2

Helar SP LL-03 0W-30

PRODUKTANBEFALING 3

Helar SP LL-03 5W-30

Skift alle 30000 km/ 24 måneder

DIFFERENTIAL BAG- MELLEMESEKTION QMVH

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

DIFFERENTIAL BAG- YDERSEKTIONER QMVH

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear LS 1015

DIFFERENTIALE BAG

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

DIFFERENTIALE FOR

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

BMW (EU) X5 F15 / F85 X5 XDRIVE35I (225 KW) (2013-2018)



GEAR AUTOMATISK ZF GA8HP 8/1

Kapacitet: 8,5 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Matic 2034		

REDUKTIONSGEARKASSE ATC 45L

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Gear 1081		

HYDRAULISK BREMSE/KOBLINGSSYSTEM DSC

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Skift alle 24 måneder

ANVEND		KLIMA
Krævende		Moderat
PRODUKTANBEFALING 1		
Drauliquid-LV Super DOT 4		

Skift alle 12 måneder

SERVOSTYRING MED AKTIV FRONTSTYRING/AKTIV RULLESTABILISERING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

KØLESYSTEM

Kapacitet: 10,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant SP 11		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

PRODUKTANBEFALING

BMW (EU) X5 F15 / F85 X5 XDRIVE35I (225 KW) (2013-2018)



inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.