

BMW (USA) SERIE 1 E82 128i N52 (2007-2013)



MOTOR N52B30
Kapacitet: 6,5 liter

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

DIFFERENTIALE BAG FRA OG MED 07/2011

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

DIFFERENTIALE BAG OP TIL 07/2011

Kapacitet: 1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

GEAR AUTOMATISK GM GA6L45R (GM6) 6/1

Kapacitet: 9-10 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Skift alle 100000 mil

GEAR MANUEL Getrag GS6-17BG/DG 6/1

Kapacitet: 1,6 liter (Førstegangsupfyldning), Kapacitet: 1,5 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

BMW (USA) SERIE 1 E82 128i N52 (2007-2013)



HYDRAULISK BREMSE/KOBLINGSSYSTEM DSC

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

Skift alle 24 måneder

SERVOSTYRING MED AKTIV FRONTSTYRING/AKTIV RULLESTABILISERING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

SERVOSTYRING SEPARAT SYSTEM

Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

ATF Dexron II-D

KØLESYSTEM

Kapacitet: 8,2 liter (+ manuel transmission/transaksel), Kapacitet: 8,4 liter (med automatisk kraftoverføring)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 11

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.