## **BMW (EU) 3 SERIES E36 318IS** (1995-1999)



| ENGINE M44<br>Capacity: 5 liter |                          |                          |
|---------------------------------|--------------------------|--------------------------|
| USE                             |                          | CLIMATE                  |
| Normal                          |                          | Moderate                 |
| PRODUCT RECOMMENDATION 1        | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar 0W-40                     | Emperol 5W-40            | Emperol 10W-40           |
| USE                             |                          | CLIMATE                  |
| Normal                          |                          | Cold                     |
| PRODUCT RECOMMENDATION 1        |                          |                          |
| Asyntho 5W-30                   |                          |                          |
|                                 |                          |                          |

| DIFFERENTIAL REAR Capacity: 1,1 liter |                          |          |  |
|---------------------------------------|--------------------------|----------|--|
| USE                                   |                          | CLIMATE  |  |
| Normal                                |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1              | PRODUCT RECOMMENDATION 2 |          |  |
| SP Gear 1011                          | Syngear TDL 75W-90       |          |  |

| TRANSMISSION AUTOMATIC WITH BLACK RATING PLATE GM THM-R1 (A4S270/310R) 4/1 Capacity: 3,3 liter, Capacity: 7,8 liter (+ torque converter) |                          |          |  |
|--|--------------------------|----------|--|
| USE  |                          | CLIMATE  |  |
| Normal   |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1   | PRODUCT RECOMMENDATION 2 |          |  |
| SP Matic 2032  | ATF Almirol              |          |  |

| TRANSMISSION AUTOMATIC WITH GREEN RATING PLATE GM THM-R1 (A4S270/310R) 4/1 Capacity: 3,3 liter, Capacity: 7,8 liter (+ torque converter) |    |          |
|--|----|----------|
| USE  | CL | LIMATE   |
| Normal   | M  | loderate |
| PRODUCT RECOMMENDATION 1   |    |          |
| SP Matic 2032  |    |          |
|  |    |          |

## BMW (EU) 3 SERIES E36 318IS (1995-1999)



| TRANSMISSION MANUAL 5/1 Capacity: 1,1 liter |          |
|---|----------|
| USE   | CLIMATE  |
| Normal                                      | Moderate |
| PRODUCT RECOMMENDATION 1                    |          |
| ATF Dexron II-D                             |          |

| HYDRAULIC BRAKE/CLUTCH SYSTEM |                          |          |  |
|-------------------------------|--------------------------|----------|--|
| USE                           |                          | CLIMATE  |  |
| Normal                        |                          | Moderate |  |
| PRODUCT RECOMMENDATION 1      | PRODUCT RECOMMENDATION 2 |          |  |
| Drauliquid-LV Super DOT 4     | Drauliquid-S DOT 4       |          |  |
|                               |                          |          |  |

Change every 24 months

| POWER STEERING SEPARATE SYSTEM Capacity: 1,2 liter |          |
|--|----------|
| USE  | CLIMATE  |
| Normal   | Moderate |
| PRODUCT RECOMMENDATION 1                           |          |
| ATF Dexron II-D                                    |          |

| COOLING SYSTEM Capacity: 6,5 liter |          |
|------------------------------------|----------|
| USE                                | CLIMATE  |
| Normal                             | Moderate |
| PRODUCT RECOMMENDATION 1           |          |
| Coolant SP 11                      |          |
| Change every 36 months             |          |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.