BMW (EU) 5 SERIES E60 / E61 525D (2007-2010)



ENGINE M57TU2 Capacity: 7,5 liter (Black dipstick (ring)), Capacity: 7,7 liter (Red dipstick (ring))			
USE		CLIMATE	
Flexible (max)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Helar SP LL-03 5W-30	Presteza MSP 5W-30	Helar MSP+ 5W-40	

Change every 30000 km/24 months

DIFFERENTIAL REAR 215K Capacity: 1,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

TRANSMISSION AUTOMATIC ZF 6HP19 6/1 Capacity: 9-9,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		

TRANSMISSION MANUAL ZF GS6-53BZ/DZ 6/1 Capacity: 1,9-2,5 liter (Initial fill), Capacity: 1,7-2,3 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear 5015		

TRANSMISSION MANUAL WITH MTF-LT3 LABEL ZF GS6-53BZ/DZ 6/1 Capacity: 1,9-2,5 liter (Initial fill), Capacity: 1,7-2,3 liter (Service fill)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Gear 5015			

BMW (EU) 5 SERIES E60 / E61 525D (2007-2010)



HYDRAULIC BRAKE/CLUTCH SYSTEM DSC	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-LV Super DOT 4	
Change every 24 months	
POWER STEERING WITH ACTIVE FRONT STEERING/ ACTIV	E ROLL STABILIZATION
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	
·	
POWER STEERING COMBINED WITH LEVELLING SYSTEM	
	OLIMATE
Normal	climate Moderate
	iviouerate
PRODUCT RECOMMENDATION 1 SP Fluid 3013	
3F Fidia 3013	
POWER STEERING SEPARATE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
	1
COOLING SYSTEM Capacity: 9,8 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	
Change every 48 months	ı

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.