BMW (EU) 7 SERIES E32 7301 WITH CATALYST (1987-1994)



ENGINE Capacity: 5,75 liter, Filter capacity: 0,75 liter			
USE		CLIMATE	
Flexible (on board maintenance system)		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Emperol 5W-40	Asyntho 5W-30	Emperol 10W-40	

DIFFERENTIAL REAR Capacity: 1,7 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		

TRANSMISSION AUTOMATIC ZF 4HP22 4/1 Capacity: 3 liter, Capacity: 7,5 liter (+ torque converter)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

TRANSMISSION AUTOMATIC WITH BLACK RATING PLATE ZF 5HP18 (A5S310Z) 5/1			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		

PRODUCT RECOMMENDATION 1	
Normal	Moderate
USE	CLIMATE

BMW (EU) 7 SERIES E32 730I WITH CATALYST (1987-1994)



ATF Dexron II-D	
PRODUCT RECOMMENDATION 1	
Normal	Moderate
USE	CLIMATE
TRANSMISSION MANUAL 5/1 Capacity: 1,25 liter	

HYDRAULIC BRAKE/CLUTCH SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
	·	·	

Change every 12 months

POWER STEERING SEPARATE SYSTEM Capacity: 2,4 liter		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Dexron II-D		

COOLING SYSTEM Capacity: 12 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 11	
Change avery 24 months	

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.