

BMW (EU) X1 E84 X1 SDRIVE18D (2009-2012)

ENGINE N47D20
Capacity: 5,2 liter

| USE | | CLIMATE |
|-----------------------------|---------------------------|--------------------------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Helar SP LL-03 5W-30 | Presteza MSP 5W-30 | Helar MSP+ 5W-40 |

DIFFERENTIAL REAR AS OF 07/2011

| USE | | CLIMATE |
|--------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear TDL 75W-90 | |

DIFFERENTIAL REAR UP TO 07/2011

| USE | | CLIMATE |
|--------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 1011 | Syngear TDL 75W-90 | |

TRANSMISSION AUTOMATIC ZF GA6HP19Z/GA6HP26Z 6/1

| USE | | CLIMATE |
|--------------------------|--|----------|
| Filled for life | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Matic 4026 | | |

TRANSMISSION MANUAL Getrag GS6-17BG/DG 6/1

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Gear 5015 | | |

**HYDRAULIC BRAKE/CLUTCH SYSTEM**

| USE | | CLIMATE |
|----------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Drauliquid-LV Super DOT 4 | | |

Change every 24 months

POWER STEERING WITH ACTIVE FRONT STEERING/ ACTIVE ROLL STABILIZATION

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| SP Fluid 3013 | | |

POWER STEERING SEPARATE SYSTEM

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| ATF Dexron II-D | | |

COOLING SYSTEM

Capacity: 7,5 liter

| USE | | CLIMATE |
|--------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant SP 11 | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.