

BUICK (USA / CAN) LACROSSE, ALLURE

LACROSSE, ALLURE 2.4L VVT (2010-2011)



MOTOR LAF
Kapacitet: 4,7 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Xedoz FE 5W-30

Skift alle 40000 km/ 12 måneder

TRANSAKSEL AUTOMATISK 6/1
Kapacitet: 8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 12 måneder, skift alle 160000 km

ANVEND

Krævende

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

Kontroller alle 12 måneder, skift alle 80000 km

HYDRAULISK BREMSESYSTEM
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid DOT 3

SERVOSTYRING
Kapacitet: 0-0 liter (Imellem min. og max.)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4036

BUICK (USA / CAN) LACROSSE, ALLURE LACROSSE, ALLURE 2.4L VVT (2010-2011)



KØLESYSTEM

Kapacitet: 7,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15

PRODUKTANBEFALING 2

Coolant SP 15+

Kontroller alle 12 måneder, skift alle 240000 km/ 60 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.