

# BUICK (USA / CAN) LACROSSE, ALLURE

## LACROSSE, ALLURE 2.4L VVT (2010-2011)



**ENGINE LAF**  
Capacity: 4,7 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
<b>Presteza MSP 5W-30</b>	<b>Xedoz FE 5W-30</b>

*Change every 40000 km/ 12 months*

**TRANSAXLE AUTOMATIC 6/1**  
Capacity: 8 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 12 months, change every 160000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 12 months, change every 80000 km*

**HYDRAULIC BRAKE SYSTEM**  
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

**POWER STEERING**  
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

**BUICK (USA / CAN) LACROSSE, ALLURE  
LACROSSE, ALLURE 2.4L VVT (2010-2011)****COOLING SYSTEM**

Capacity: 7,1 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Coolant SP 15****PRODUCT RECOMMENDATION 2****Coolant SP 15+***Check every 12 months, change every 240000 km/ 60 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*