

CADILLAC (USA / CAN) BLS BLS 2.0T FLEXPOWER (2007-2009)



MOTOR B207L BioPower

Kapacitet: 6,75 liter (Førstegangsupfyldning), Kapacitet: 6 liter (Servicepåfyldning)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Helar MSP+ 5W-40

PRODUKTANBEFALING 3

Specialsynth MSP 5W-40

Skift alle 15000 km/ 12 måneder

TRANSAKSEL AUTOMATISK 5/1

Kapacitet: 3,25 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 30000 km/ 12 måneder, skift alle 120000 km/ 72 måneder

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,9 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Kontroller alle 12 måneder/ 30000 km

TRANSAKSEL MANUEL F40 6/1

Kapacitet: 2,2 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1011

PRODUKTANBEFALING 2

Syngear TDL 75W-90

Kontroller alle 12 måneder/ 30000 km

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 0,43 liter (Højrestyring), Kapacitet: 0,37 liter (Venstrestyring)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Kontroller alle 30000 km/ 12 måneder, skift alle 48 måneder

CADILLAC (USA / CAN) BLS BLS 2.0T FLEXPOWER (2007-2009)



SERVOSTYRING

Kapacitet: 1,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 12 måneder/ 30000 km

KØLESYSTEM

Kapacitet: 7,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

Kontroller alle 12 måneder/ 30000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.