## CADILLAC (USA / CAN) ATS(-V) ATS 2.5 (2012-2014)



## ENGINE LCV Ecotec

Capacity: 4,7 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	

DIFFERENTIAL REAR LIMITED SLIP				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear LS 1015				
Change every 84000 km	-			
USE		CLIMATE		
Severe		Moderate		
PRODUCT RECOMMENDATION 1				
SP Gear LS 1015				
Character average 72000 km	•	•		

Change every 72000 km

TRANSMISSION AUTOMATIC Hydra-Matic 6L45 6/1 Capacity: 6 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
SP Matic 4036				
Change every 156000 km				

USE CLIMATE Severe Moderate PRODUCT RECOMMENDATION 1 SP Matic 4036

Change every 72000 km

## CADILLAC (USA / CAN) ATS(-V) ATS 2.5 (2012-2014)



HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Drauliquid DOT 3				

COOLING SYSTEM Capacity: 6,6 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Change every 240000 km/ 60 month	S	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or

In the data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.