CADILLAC (USA / CAN) CTS(-V) CTS 3.6 V6 (2010-2010)



| ENGINE LLT Capacity: 5,7 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Flexible (max) | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Presteza MSP 5W-30 | Xedoz FE 5W-30 | |
| 0/ / / / / / / / / / / / / / / / / / / | | · |

Change every 40000 km

DIFFERENTIAL REAR

We are unable to give a standard recommendation for this component. Please contact our service department.

| TRANSMISSION AUTOMATIC 6L90 6/1 Capacity: 6,3 liter | |
|--|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4036 | |
| Change every 160000 km | |
| USE | CLIMATE |
| | |

| Severe | Moderate |
|--------------------------|----------|
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 4036 | |
| Change every 80000 km | · |

| HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.) | | |
|--|--|---------------------|
| use Normal | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Drauliquid DOT 3 | | |

| HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.) | | |
|---|---|---------------------|
| use Normal | | climate Moderate |
| PRODUCT RECOMMENDATION 1 Drauliquid-LV Super DOT 4 | PRODUCT RECOMMENDATION 2 Drauliquid-S DOT 4 | |

CADILLAC (USA / CAN) CTS(-V) CTS 3.6 V6 (2010-2010)



| POWER STEERING | |
|--------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| SP Matic 2032 | |

| COOLING SYSTEM Capacity: 10,3 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Coolant SP 15 | Coolant SP 15+ | |
| Change every 240000 km/ 60 months | | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.