

CADILLAC (USA / CAN) CTS(-V) CTS 3.6 V6 (2012-2013)



ENGINE LFX
Capacity: 5,7 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

Change every 12 months

DIFFERENTIAL REAR

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

TRANSMISSION AUTOMATIC Hydra-Matic 6L45 6/1
Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Change every 156000 km

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Change every 72000 km

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

CADILLAC (USA / CAN) CTS(-V) CTS 3.6 V6 (2012-2013)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

COOLING SYSTEM

Capacity: 11,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Change every 240000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.