CADILLAC (USA / CAN) CTS(-V) CTS 3.6 V6 (2014-2015)



ENGINE LFX Capacity: 5,7 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 5W-30	
01 10 11	·

Change every 12 months

DIFFERENTIAL REAR		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1011	Syngear TDL 75W-90	
Change aver 72000 km	I	

Change every 72000 km

DIFFERENTIAL REAR LIMITED SLIP Capacity: 1,2 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear LS 1015	

Change every 72000 km

TRANSMISSION AUTOMATIC Aisin Warner TL-80SN 8/1			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1			
SP Matic 4036			
Change every 72000 km			

CADILLAC (USA / CAN) CTS(-V) CTS 3.6 V6 (2014-2015)



TRANSMISSION AUTOMATIC Hydra-Matic 6L45 6/1 Capacity: 6 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4036		
70,000 /		

Change every 72000 km

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 72000 km/ 36 months	·	

COOLING SYSTEM Capacity: 11,3 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Change every 240000 km/ 60 months			

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.