TRANSMISSION AUTOMATIC 6L90 6/1

CADILLAC (USA / CAN) CTS(-V) CTS-V 6.2 V8 (2011-2014)



ENGINE LSA Capacity: 5,7 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 5W-30	
Change every 12 months	

DIFFERENTIAL REAR LIMITED SLIP		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Gear LS 1015		
USE		CLIMATE
use Severe		climate Moderate
Severe		

Capacity: 6,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 156000 km	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 72000 km	
Change every 72000 Kill	

CADILLAC (USA / CAN) CTS(-V) CTS-V 6.2 V8 (2011-2014)



TRANSMISSION MANUAL Tremec TR-600 Capacity: 3,8 liter	60 6/1	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
ATF Almirol		
Change every 72000 km		

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
Change every 48000 km/24 months		

HYDRAULIC CLUTCH SYSTEM Capacity: 0-0 liter (Between min and m	nax.)		
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 48000 km/24 months		·	

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

COOLING SYSTEM Capacity: 11,8 liter, Capacity: 2,3 liter (intercooler)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 12 months, change every 240000 km/60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.