CHERY BOSS BOSS 1.8 16V (2006-2010)



| ENGINE SQR481FC Capacity: 4-4,5 liter | | |
|--|--------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Duranza LSP 5W-30 | Asyntho 5W-30 | |
| Change every 15000 km | | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Duranza LSP 5W-30 | Asyntho 5W-30 | |
| Change every 5000 km | , | , |

| TRANSAXLE MANUAL 5/1 Capacity: 2,2 liter | | | | |
|--|--------------------------|--------------------------|--|--|
| use Normal | | CLIMATE | | |
| | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| SP Gear 1011 | Syngear TDL 75W-90 | Syngear 75W-90 | | |
| Change every 30000 km/ 12 month | 18 | | | |

| HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.) | | | | |
|--|--------------------------|--------------------|--|--|
| use Normal | | сымате Moderate | | |
| | | | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | | |
| Change every 50000 km/ 24 months | | : | | |

| POWER STEERING Capacity: 0-0 liter (Between min and max.) | | | | |
|---|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| SP Matic 2032 | ATF Almirol | | | |
| Check every 15000 km | | | | |

CHERY BOSS BOSS 1.8 16V (2006-2010)



| COOLING SYSTEM Capacity: 7,5 liter | |
|------------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Coolant -38 Organic NF | |
| Change every 40000 km/24 months | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.