CHERY TENGO TENGO 2.0 (2008-2015)



ENGINE SQR484F Capacity: 4,5 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1			
Emperol 10W-40			
Change every 15000 km			
USE		CLIMATE	
Initial service		Moderate	
PRODUCT RECOMMENDATION 1			
Emperol 10W-40			
Change every 5000 km			

TRANSAXLE AUTOMATIC QR425AHA 4/1 Capacity: 2,1 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 30000 km/ 12 months		

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 50000 km/ 24 months	·		

POWER STEERING Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Matic 2032	ATF Almirol		
Check every 15000 km			

CHERY TENGO TENGO 2.0 (2008-2015)



COOLING SYSTEM Capacity: 7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Change every 40000 km/24 months	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.