

CHEVROLET (EU) (DAEWOO) ALERO

ALERO 3.4 V6 (1999-2004)



ENGINE LA1
Capacity: 4,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Asyntho 5W-30	Emperol 10W-40

Change every 15000 km/ 12 months

TRANSAXLE AUTOMATIC 4T40-E 4/1
Capacity: 6,5 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
SP Matic 2032	ATF Almirol

Check every 15000 km/ 12 months, change every 60000 km/ 48 months

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

Change every 30000 km/ 24 months

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
ATF Almirol	ATF Dexron II-D

Check every 15000 km/ 12 months

GREASE POINTS/NIPPLES

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
HT Q9 High Grade Grease	Labora Grease

Change every 15000 km/ 12 months

CHEVROLET (EU) (DAEWOO) ALERO

ALERO 3.4 V6 (1999-2004)

**COOLING SYSTEM**

Capacity: 12,9 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 15+****PRODUCT RECOMMENDATION 2****Coolant SP 12****PRODUCT RECOMMENDATION 3****Coolant -38 Organic NF***Change every 60000 km/ 48 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.