CHEVROLET (USA / CAN) CAMARO CAMARO 6.2 V8 (298 KW) (2011-2012)



ENGINE L99 Capacity: 7,6 liter	
USE	CLIMATE
Flexible (max)	Moderate
PRODUCT RECOMMENDATION 1	
Presteza MSP 5W-30	
Change every 7500 miles/ 12 months	

DIFFERENTIAL REAR Capacity: 0,9 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
Change every 97500 miles			
USE		CLIMATE	
Severe		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
SP Gear 1011	Syngear TDL 75W-90		
Change every 37500 miles	'		

Capacity: 0,9 liter, Capacity: 75 CM3 (LS-additive)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
SP Gear LS 1015			
Change every 97500 miles			
USE	CLIMATE		
Severe	Moderate		
PRODUCT RECOMMENDATION 1			
SP Gear LS 1015			
Change every 37500 miles			

CHEVROLET (USA / CAN) CAMARO CAMARO 6.2 V8 (298 KW) (2011-2012)



TRANSMISSION AUTOMATIC 6/1 Capacity: 6,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 97500 miles	
USE	CLIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4036	
Change every 37500 miles	
-	

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 12 months, change every 24 months	'

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2032	

COOLING SYSTEM Capacity: 10,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Charle ayon, 12 months abonds a	150000 miles/00 mentles	·	

Check every 12 months, change every 150000 miles/60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.