

CHEVROLET (USA / CAN) CAMARO

CAMARO 6.2 V8 (318 KW) (2011-2012)



ENGINE LS3
Capacity: 7,6 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

Change every 7500 miles/ 12 months

DIFFERENTIAL REAR LIMITED SLIP

Capacity: 0,9 liter, Capacity: 75 CM3 (LS-additive)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

Change every 97500 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear LS 1015

Change every 45000 miles

TRANSMISSION MANUAL 6/1

Capacity: 3,9 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Almirol

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

Check every 12 months, change every 24 months

CHEVROLET (USA / CAN) CAMARO

CAMARO 6.2 V8 (318 KW) (2011-2012)



POWER STEERING

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 2032		

COOLING SYSTEM

Capacity: 11,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	

Check every 12 months, change every 150000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.