

# CHEVROLET (USA / CAN) COBALT COBALT

## 2.4 16V (2006-2006)



**ENGINE LE5**  
Capacity: 4,7 liter

| USE                       |                          | CLIMATE  |
|---------------------------|--------------------------|----------|
| Flexible (max)            |                          | Moderate |
| PRODUCT RECOMMENDATION 1  | PRODUCT RECOMMENDATION 2 |          |
| <b>Presteza MSP 5W-30</b> | <b>Xedoz FE 5W-30</b>    |          |

*Change every 12 months*

**TRANSAXLE AUTOMATIC 4/1**  
Capacity: 6,6 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Severe                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

*Change every 50000 miles*

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Filled for life          |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

**TRANSAXLE MANUAL 5/1**  
Capacity: 1,6 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Matic 2032</b>     | <b>ATF Almirol</b>       |          |

### HYDRAULIC BRAKE SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

# CHEVROLET (USA / CAN) COBALT COBALT

## 2.4 16V (2006-2006)



### HYDRAULIC CLUTCH SYSTEM

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>Drauliquid DOT 3</b>  |  |          |

### GREASE POINTS/NIPPLES

| USE                      |                                 | CLIMATE                      |
|--------------------------|---------------------------------|------------------------------|
| Normal                   |                                 | Moderate                     |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2        | PRODUCT RECOMMENDATION 3     |
| <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> | <b>MP Lithep Grease EP 2</b> |

*Change every 12 months*

### COOLING SYSTEM

Capacity: 7 liter

| USE                      |                          | CLIMATE                       |
|--------------------------|--------------------------|-------------------------------|
| Normal                   |                          | Moderate                      |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3      |
| <b>Coolant SP 15+</b>    | <b>Coolant SP 12</b>     | <b>Coolant -38 Organic NF</b> |

*Check every 12 months, change every 150000 miles/ 60 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*