

CHEVROLET (USA / CAN) EXPRESS

GMT610 EXPRESS 5.3 V8 (2007-2010)



ENGINE LMF
Capacity: 5,7 liter

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Presteza MSP 5W-30

PRODUCT RECOMMENDATION 2

Xedoz FE 5W-30

Change every 12 months

DIFFERENTIAL REAR
Capacity: 2,03-3,13 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

TRANSMISSION AUTOMATIC 4L60-E 4/1
Capacity: 4,7 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Check every 6 months, change every 100000 miles

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036

Check every 6 months, change every 50000 miles

CHEVROLET (USA / CAN) EXPRESS

GMT610 EXPRESS 5.3 V8 (2007-2010)


TRANSMISSION AUTOMATIC 4L80-E 4/1

Capacity: 7,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 6 months, change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 6 months, change every 50000 miles*
TRANSMISSION AUTOMATIC 6L90-E 6/1

Capacity: 6 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 6 months, change every 100000 miles*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036*Check every 6 months, change every 50000 miles*
HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3*Check every 12 months*
POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Almirol

CHEVROLET (USA / CAN) EXPRESS

GMT610 EXPRESS 5.3 V8 (2007-2010)



WHEEL BEARINGS FRONT

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

HT Q9 High Grade Grease

COOLING SYSTEM

Capacity: 12,7 liter, Capacity: 15,5 liter (+ rear heater)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 15

PRODUCT RECOMMENDATION 2

Coolant SP 15+

Check every 6 months, change every 150000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.