## CHEVROLET (USA / CAN) SPARK M300 SPARK 1.2 (2014-2016)



ENGINE LL0 Capacity: 3,8 liter	
USE	CLIMATE
Flexible (max)	Arctic
PRODUCT RECOMMENDATION 1	
Presteza MSP 0W-20	
Change every 7500 miles/ 12 months	

TRANSAXLE CVT M4M-CVT7 1/1
Capacity: 8 liter

USE

Normal

PRODUCT RECOMMENDATION 1

SP Matic 4016

Check every 7500 miles

TRANSAXLE MANUAL Y4M-HD 5/1
Capacity: 2,1 liter

USE

Normal

PRODUCT RECOMMENDATION 1

SP Gear 5015

Check every 7500 miles

HYDRAULIC BRAKE/CLUTCH SYSTEM Capacity: 0,5 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Check every 7500 miles, change every 45000 miles/ 36 months				

COOLING SYSTEM Capacity: 4,8 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Coolant SP 15	Coolant SP 15+		
Chook ayan, 7500 milas ahanga a	vary 150000 miles/60 menths	·	

Check every 7500 miles, change every 150000 miles/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is

PRODUCT RECOMMENDATION

## CHEVROLET (USA / CAN) SPARK M300 SPARK 1.2 (2014-2016)



advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.