CHEVROLET (USA / CAN) SUBURBAN GMT830 SUBURBAN 6.0 V8 (2001-2005)



ENGINE LQ4 Capacity: 5,7 liter, Filter capacity: 0,95 liter		
USE		CLIMATE
Flexible (max)		Moderate
PRODUCT RECOMMENDATION 1		
Asyntho 5W-30		
Change every 12 months		

DIFFERENTIAL REAR LIMITED SLIP	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Gear LS 1015	
Check every 12500 km/ 12 months	

DIFFERENTIAL REAR STEERABLE AXLE		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
SP Gear LS 1015		
Check every 12500 km/ 12 months	'	

TRANSMISSION AUTOMATIC 4L80-E 4/1 Capacity: 7,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Matic 2032	ATF Almirol	
Check every 6 months, change every 166000 km		

HYDRAULIC BRAKE SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	
Check every 12500 km/ 12 months	

CHEVROLET (USA / CAN) SUBURBAN GMT830 SUBURBAN 6.0 V8 (2001-2005)



POWER STEERING		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
ATF Almirol		
Check every 12500 km/ 12 months	·	

GREASE POINTS/NIPPLES		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
HT Q9 High Grade Grease	Labora Grease	Q5 MP Calcep Grease EP 2
Chook ayon, 12500 km/12 months	-	'

Check every 12500 km/ 12 months

COOLING SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15	Coolant SP 15+	
Charles war 40,500 km/ 40 months about a charge and 40,000 km/ 60 months		

Check every 12500 km/ 12 months, change every 240000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.