

# CHEVROLET (USA / CAN) SUBURBAN

## GMT931 SUBURBAN 5.3 V8 (2007-2010)

**ENGINE**

Capacity: 5,7 liter, Filter capacity: 0,5 liter

**USE**

Flexible (max)

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****Presteza MSP 5W-30****PRODUCT RECOMMENDATION 2****Xedoz FE 5W-30***Change every 12 months***DIFFERENTIAL REAR**

Capacity: 2,03-3 liter

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Gear LS 1015****TRANSMISSION AUTOMATIC 4/1**

Capacity: 4,7 liter, Capacity: 10,6 liter (Overhaul capacity)

**USE**

Normal

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 4036***Check every 12 months, change every 160000 km***USE**

Severe

**CLIMATE**

Moderate

**PRODUCT RECOMMENDATION 1****SP Matic 4036***Check every 12 months, change every 80000 km*

# CHEVROLET (USA / CAN) SUBURBAN GMT931 SUBURBAN 5.3 V8 (2007-2010)



**TRANSMISSION AUTOMATIC 4L80-E 4/1**  
Capacity: 7,3 liter, Capacity: 12,8 liter (Overhaul capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 12 months, change every 160000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 12 months, change every 80000 km*

**TRANSMISSION AUTOMATIC 6/1**  
Capacity: 5,7 liter, Capacity: 9,9 liter (Overhaul capacity)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 12 months, change every 160000 km*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 4036</b>		

*Check every 12 months, change every 80000 km*

## HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>Drauliquid DOT 3</b>		

## POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
<b>SP Matic 2032</b>		

# CHEVROLET (USA / CAN) SUBURBAN GMT931 SUBURBAN 5.3 V8 (2007-2010)



## GREASE POINTS/NIPPLES

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>HT Q9 High Grade Grease</b>	<b>Labora Grease</b>	<b>Q5 MP Calcep Grease EP 2</b>

## COOLING SYSTEM

Capacity: 17,3 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Coolant SP 15+</b>	<b>Coolant SP 12</b>	<b>Coolant -38 Organic NF</b>

*Check every 12 months, change every 240000 km/ 60 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*