

# CHEVROLET (USA / CAN) TRAILBLAZER

## TRAILBLAZER SS 6.0 V8 (2005-2009)



**ENGINE** LS2  
Capacity: 5,7 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Presteza MSP 5W-30**

PRODUCT RECOMMENDATION 2

**Xedoz FE 5W-30**

*Change every 12 months*

### DIFFERENTIAL REAR LIMITED SLIP

USE

Filled for life

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Gear LS 1015**

### TRANSMISSION AUTOMATIC 4/1

Capacity: 4,7 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**SP Matic 4036**

*Check every 12 months, change every 100000 miles*

### HYDRAULIC BRAKE SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

*Check every 12 months*

### HYDRAULIC CLUTCH SYSTEM

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3**

*Check every 12 months*

# CHEVROLET (USA / CAN) TRAILBLAZER

## TRAILBLAZER SS 6.0 V8 (2005-2009)



### POWER STEERING

| USE                      |  | CLIMATE  |
|--------------------------|--|----------|
| Normal                   |  | Moderate |
| PRODUCT RECOMMENDATION 1 |  |          |
| <b>ATF Almirol</b>       |  |          |

*Check every 12 months*

### GREASE POINTS/NIPPLES

| USE                            |                          | CLIMATE                         |
|--------------------------------|--------------------------|---------------------------------|
| Normal                         |                          | Moderate                        |
| PRODUCT RECOMMENDATION 1       | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3        |
| <b>HT Q9 High Grade Grease</b> | <b>Labora Grease</b>     | <b>Q5 MP Calcep Grease EP 2</b> |

*Check every 12 months*

### COOLING SYSTEM

Capacity: 10,6 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>Coolant SP 15</b>     | <b>Coolant SP 15+</b>    |          |

*Check every 12 months, change every 150000 miles/ 60 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*