CHRYSLER (USA / CAN) 300 LX 300 3.6 V6 (2012-2014)



ENGINE Pentastar Capacity: 5,6 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Duranza ECO 5W-20	
01 00000 11 / 0 11	

Change every 8000 miles/ 6 months

DIFFERENTIAL REAR Capacity: 1,1-1,3 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Check every 20000 miles/ 24 months	
USE	CLIMATE

052	OCIMATE
Severe	Moderate
PRODUCT RECOMMENDATION 1	
Gearlube Racing 75W-140	
Change every 40000 miles/ 48 months	

TRANSMISSION AUTOMATIC 8HP45 8/ Capacity: 9 liter (Dry fill)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 2034	

CHRYSLER (USA / CAN) 300 LX 300 3.6 V6 (2012-2014)



TRANSMISSION AUTOMATIC W5A580 5/1 Capacity: 7,7 liter (Dry fill), Capacity: 5 liter (Service fill)		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change every 144 months/ 120000 miles		
USE		CLIMATE
Severe		Moderate
PRODUCT RECOMMENDATION 1		
SP Matic 4026		
Change avery 60000 miles/72 months		

Change every 60000 miles/72 months

HYDRAULIC BRAKE SYSTEM		
Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		
		_

POWER STEERING	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Fluid 3013	

COOLING SYSTEM Capacity: 10,5 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Coolant SP 15+	Coolant SP 12	
Change over 150000 miles / 120 months	•	

Change every 150000 miles/ 120 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.