

CHRYSLER (USA / CAN) 300 LX 300 5.7 HEMI V8 AWD (2011-2012)



ENGINE HEMI
Capacity: 6,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20

Change every 8000 miles/ 6 months

DIFFERENTIAL FRONT
Capacity: 0,6 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

Check every 24000 miles/ 18 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1011

PRODUCT RECOMMENDATION 2

Syngear TDL 75W-90

PRODUCT RECOMMENDATION 3

Syngear 75W-90

Change every 48000 miles/ 36 months

DIFFERENTIAL REAR
Capacity: 1,1-1,3 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Check every 24000 miles/ 18 months

USE
Severe

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Gearlube Racing 75W-140

Change every 48000 miles/ 36 months

CHRYSLER (USA / CAN) 300 LX 300 5.7 HEMI V8 AWD (2011-2012)



TRANSFERBOX Borg Warner 44-40
Capacity: 1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Check every 32000 miles/ 24 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 2032		

Change every 64000 miles/ 48 months

TRANSMISSION AUTOMATIC W5A580 5/1
Capacity: 7,7 liter (Dry fill), Capacity: 5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 120000 miles/ 90 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1		
SP Matic 4026		

Change every 64000 miles/ 48 months

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Drauliquid DOT 3		

POWER STEERING

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
SP Fluid 3013		

CHRYSLER (USA / CAN) 300 LX 300 5.7 HEMI V8 AWD (2011-2012)

**COOLING SYSTEM**

Capacity: 13,9-14,3 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant SP 12 EVO***Change every 104000 miles/ 60 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.